

GL-RG-52M

2°C~8°C Pharmacy Refrigerator

GENERAL SPECIFICATIONS

Cabinet Type	Upright
Capacity	1505 L / 53.14 cu ft
Internal Size(W*D*H)	1685*670*1514mm / 66.33*26.37*59.6in
External Size(W*D*H)	1795*830*1990mm / 70.66*32.67*78.34in
Package Size(W*D*H)	1918*928*2193mm / 75.51*36.53*86.33in
NW/GW(Kgs)	322/430

PERFORMANCE

Temperature Range	2~8°C
Ambient Temperature	16-32°C
Cooling Performance	4°C
Climate Class	N
Controller	Microprocessor
Display	Digital display

REFRIGERATION

Compressor	1pc
Cooling Method	Air cooling
Defrost Mode	Automatic
Refrigerant	R290
Insulation Thickness(mm)	55

CONSTRUCTION

External Material	Powder coated material
Inner Material	Stainless steel
Shelves	18(coated steel wired shelf)
Door Lock with Key	Yes
Lighting	LED
Access Port	1pc. Ø 25 mm
Casters	6(6 caster with brake)
Data Logging/Interval/RT	USB/Record every 10 minute / 2 years
Backup Battery	yes

ALARM

Temperature	High/Low temperature,High ambient temperature,Condenser high temperature
Electrical	Power failure , Low battery
System	Sensor error,Door ajar, Built-in datalogger USB Failure, Remote alarm

ELECTRICAL

Power Supply(V/Hz)	220/50 / 110/60
Rated Power(W)	1283
Power Consumption(KWh/24h)	13.22
Rated Current(A)	6.55

OPTIONS ACCESSORY

System	Printer,RS232, RS485, Remote alarm contact Backup battery
--------	--

