

GL-RF-10M

2°C~8°C / -10°C~-26°C Medical Combined Refrigerator & Freezer

GENERAL SPECIFICATIONS

Capacity	289L / 10.20cu ft , R: 189L / 6.67 cu ft , F: 100L / 3.53 cu ft
Internal Size(W*D*H)	R: 600*510*670mm, F: 500*460*505mm
External Size(W*D*H)	745*650*1845mm / 29.37*25.59*72.63in
Package Size(W*D*H)	830*750*1945mm / 32.67*29.52*76.57in
NW/GW(Kgs)	140/162

PERFORMANCE

Temperature Range	R: 2~8°C, F: -10~-26°C
Ambient Temperature	16-32°C
Cooling Performance	R: 4, F: -25°C
Climate Class	N
Controller	Microprocessor
Display	Digital display

REFRIGERATION

Compressor	2pcs
Cooling Method	R: Forced air cooling , F: Direct cooling
Defrost Mode	R: Automatic, F: Manual
Refrigerant	R134a
Insulation Thickness(mm)	R: 50, F: 100

CONSTRUCTION

External Material	Carbon steel spraying
Inner Material	304 Stainless steel
Shelves	R: 3+1(stainless steel), F: 3(ABS)
Backup battery	Yes
External Lock	Yes
Access Port	2pcs. Ø 25 mm
Casters	4(2 caster with brake)+ (2 leveling feet)
Data Logging/Interval/RT	USB/Record every 10 minute / 2 years
Door with Heater	yes
Standard Accessory	RS485, Remote alarm contact

ALARM

Temperature	High/Low temperature, High ambient temperature .
Electrical	Power failure, Low battery
System	Sensor error, Door ajar, USB datalog failure, Communication failure, Remote alarm

ELECTRICAL

Power Supply(V/HZ)	220/50 / 110/60
Rated Power(W)	295
Power Consumption(KWh/24h)	3.11
Rated Current(A)	2.23

OPTIONS ACCESSORY

System	RS232
--------	-------

