

**GL-RF-19M**

2°C~8°C / -10°C~-26°C Medical Combined Refrigerator &amp; Freezer

**GENERAL SPECIFICATIONS**

Capacity	519L 18.32cu ft; <b>R:</b> 323L/11.40cu ft; <b>F:</b> 196L / 6.92cu ft
Internal Size(W*D*H)	<b>R:</b> 750*610*740mm, <b>F:</b> 650*560*565mm
External Size(W*D*H)	910*740*1972mm / 35.82*29.13*77.63in
Package Size(W*D*H)	960*855*2140mm / 37.79*33.66*84.25in
NW/GW(Kgs)	186/215

**PERFORMANCE**

Temperature Range	<b>R:</b> 2~8°C, <b>F:</b> -10~-26°C
Ambient Temperature	16-32°C
Cooling Performance	<b>R:</b> 5, <b>F:</b> -26°C
Climate Class	N
Controller	Microprocessor
Display	Digital display

**REFRIGERATION**

Compressor	2pcs
Cooling Method	<b>R:</b> Forced air cooling , <b>F:</b> Direct cooling
Defrost Mode	<b>R:</b> Automatic, <b>F:</b> Manual
Refrigerant	R600a
Insulation Thickness(mm)	<b>R:</b> 50, <b>F:</b> 100

**CONSTRUCTION**

External Material	Spraying steel plate
Inner Material	Stainless steel
Shelves	<b>R:</b> 3+1(stainless steel), <b>F:</b> 6(ABS)
Door Lock with Key	Yes
Lighting	LED
Access Port	2pcs. Ø 25 mm
Casters	4(2 caster with brake)
Data Logging/Interval/RT	USB/Record every 10 minute / 2 years
Door with Heater	yes
Backup Battery	yes

**ALARM**

Temperature	High/Low temperature, High ambient temperature .
Electrical	Power failure,Low battery
System	Sensor error, Door ajar, USB datalog failure, Communication failure

**ELECTRICAL**

Power Supply(V/HZ)	220/50 / 110/60
Rated Power(W)	382
Power Consumption(KWh/24h)	3.76
Rated Current(A)	2.54

**OPTIONS ACCESSORY**

System	Printer, RS485, RS232, Remote alarm contact
--------	---

